

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (previously presented): A network status reporting method for reporting in a communications network a network status information to a data source with an adaptive transmission rate in order to enable said data source to adapt said transmission rate based on said network status information, said communications network further comprising at least one intermediate network node, and a data sink, wherein only said data sink reports to said data source on said network status information of said communications network in a neighbourhood around the data sink, and wherein no intermediate network node reports to said data source on said network status information of said communications network.

2. (previously presented): A communications network comprising:  
at least one data source with an adaptive transmission rate;  
at least one intermediate node; and  
at least one data sink,  
wherein said data source adapts said transmission rate on the basis of network status information, and wherein only said data sink is able to report said network status information of said communications network in a neighbourhood of the data sink to said data source and no intermediate node is able to report network status information to said data source.

3. (previously presented): Communications network according to claim 2, wherein said data sink is a line termination in an access network of said communications network.

4. (previously presented): Communications network according to claim 2, wherein said data sink is a network termination in an access network of said communications network.

5. (previously presented): Communications network according to claim 3, wherein said network status information is a capacity of a link between a network termination and a line termination in said access network of said communications network.

6. (previously presented): The data source adapted to be used in the communications network according to claim 2.

7. (previously presented): The data sink adapted to be used in the communications network according to claim 2.

8. (previously presented): The data source according to claim 6, wherein said data source is adapted to request said data sink to report to said data source on said network status information of said communications network.

9. (previously presented): Data sink according to claim 7, wherein said data sink is adapted to regularly report to said data source on said network status information of said communications network.

10. (previously presented): A communications system comprising:

- a data source with an adaptive transmission rate;
- a line termination element;
- a network termination element connected to the line termination element via a first network; and
- at least one intermediate node connecting the data source to the line termination element via a second network;

wherein the data source adapts the transmission rate on the basis of a network status reported by at least one of the line termination element and the network termination element, and wherein the network status is determined based on a quality of signal of the first network only.

11. (previously presented): The communications system according to claim 10, wherein the first network is of a different type than the second network, and comprise a heterogeneous network system.

12. (previously presented): The communications system according to claim 10, wherein the line termination element and the network termination element negotiate a transmission rate

for the first network, and wherein one of the line termination element and the network termination element reports the network status only when the transmission rate in the first network is changed.

13. (previously presented): The communication system according to claim 12, wherein the network termination element detects an influence of environmental conditions on the transmission rate of the first network and, based on the detected influence, the network termination element and the line termination element re-negotiate the transmission rate.

14. (previously presented): The communication system according to claim 10, wherein the first network comprises a digital subscriber line and wherein the second network comprises a frame relay network, and wherein the network termination element comprises a modem and the line termination element comprises a multiplexer.

15. (previously presented): A network status reporting method comprising:  
a data sink reporting to a data source status information of a first communication network connected to the data sink;  
at least one intermediate network node transmitting said report in a second communication network connected to the data source; and  
said data source adjusting transmission rate based on said received report,

wherein only said data sink reports to said data source on said status of said first communications network, and none of said at least one intermediate network node report to said data source on said network status of said second communications network near said at least one intermediate network node.

16. (previously presented): The communication network according to claim 2, wherein:  
the network status information is information about the status of a network segment around the data sink,

the network status information comprises a report about at least one of: congestion, radio-frequency interference, and weather condition in the network segment around the data sink, and  
the report is communicated to the data source.

17. (previously presented): The communication system according to claim 10, wherein  
the line termination element is a data sink.

18. (previously presented): The communication system according to claim 15, wherein  
the data sink is connected to a modem via the first communication network and wherein said modem is connected to the data source via the at least one intermediate network node of the second communication network.

19. (previously presented): The communication system according to claim 18, wherein the second communication network is internet and wherein the first communication network is public switch telephone network.

20. (currently amended): The communication system according to claim 15, wherein the data sink is connected to a network termination element via the first communication network and wherein said network termination element is connected to the data source via the at least one intermediate network node of the second communication network and wherein the second communication network is ~~internet~~ frame relay network.

21. (currently amended): The communication system according to claim 15, wherein the data sink reports to the data source the status information of the first communication network connected to the data sink only when a change in status of the first communication network occurs and wherein at least one of the first communication network and the second communication network is not adapted to perform available bit rate control technique.